

STIKCAM[®]

Camera on a Stick

'seeing is believing'

Stikcam™, is the simple way to achieve extreme close ups, fast flowing pans and other exciting options with the minimum of set-up and technical intervention. Stikcam is easily set up and operated by a single person. It's robust jib arm provides crane shots in confined and extreme places, unreachable with conventional systems. In fact Stikcam is as versatile as your imagination. It can get you to the front of the scrum for a grabbed interview, on stage at a rock concert, without you ever coming between the audience and the talent. There is no attachment to the body allowing greater freedom of movement and increased safety in extreme conditions, although it may be mounted on a harness or tripod. The use of ultra light materials and simple design ensures low maintenance with little user adjustment.



FEATURES

- Mechanical Pan and Tilt Head
- Hard Anodised
- Titanium Camera Protection
- Fully waterproof
- Rust Proof
- Extremely light weight
- Changeable pivot point
- Extremely Rugged
- Multiple Camera Mounts
- Gimble Tripod mounts
- Body Harness

BENEFITS

- Can be located in discreet locations
- Left-hand and right-hand operation
- Rig time less than 1 minute
- Single man use
- Improves safety in Hazardous environments.
- Easy operation
-

Stikcam® is a low-cost, highly versatile miniature jib arm. Extreme shots, setup, reliability

*IOV Winner -
Best Corporate Video 2004*

1.0 Available Cameras

Toshiba TU62/TU63 head with TU61 CCU
Optional SDI output

Hitachi HV-D37/D27

Panasonic GP-US522HA/532/542

Sony DXC-C33

Ikegami HDL-20 HIGH DEFINITION

RiverCam™

Waterproof

Intrinsically Safe iCam 100

700/800 Resolution



750/800 rESOLUTION




700/800 Resolution



850 Resolution



1000 Resolution



570 Resolution
4 EXT bright LED
100meters



380 TV Lines 0.5lux

2.0 Options

Waterproof Camera for any above camera with/without LED Underwater lights

Zoom Lens For any above camerasMicro

Pan and tilt head

Remote control of camera and recorder

Anamorphic Adaptors for above 4:3—16:9

3.0 Recorders

DSR-V10



DSR-50



Puddlecam® all in one

4:3 16:9 Switchable

4.0 Monitor

5.0 Mechanical

Length Overall

2400 mm

Fold Down Length

1400 mm

Diameter

26mm

Max Load at full extent

1.5 KG

Weight (Dry)

1 Kg

Pan/Tilt Angle

90 Degrees

Camera Mount

1/4 UNC